

SPECIFICATION SHEET

JFW MODEL 75P-223

**SOLID STATE PROGRAMMABLE
ATTENUATOR**

JFW Industries, Inc.
Phone: 317-887-1340
sales@jfwindustries.com
www.jfwindustries.com

Frequency Range 5-2150 MHz

Impedance 50 Ohms nominal

Attenuation Range 0-63.75 dB in 0.25 dB steps

Attenuation Steps 0.25, 0.5, 1, 2, 4, 8, 16 and 32 dB

VSWR 2.0:1 maximum
< 1.6:1 typical 5-1218 MHz
< 1.8:1 typical 1218-2150 MHz

Attenuation Accuracy (guaranteed monotonic) ± 0.15 dB 0.25-4.00 dB
± 0.25 dB 4.25-16.00 dB
± 0.50 dB or 2% 16.25-63.75 dB
(whichever is greater)

Insertion Loss 5 dB maximum
2.0 dB typical @ 5 MHz
3.9 dB typical @ 1218 MHz
4.5 dB typical @ 2150 MHz

RF Input Power +23 dBm 5-100 MHz
+27 dBm 100-2150 MHz

Switching Speed 2 microseconds maximum
0.7 microseconds typical

DC Supply +5Vdc @ 2mA nominal

Control Logic (8 Lines) TTL Low for Thru Path
TTL High for Attenuation

DC Connector 3M #D2510-6002
(Mating Connector 3M #3473-6610)

RF Connector F, BNC, or N female

Operating Temperature Range -40°C to +85°C

Physical Size See outline drawings:
092-8652-26 (F)

ECR/ECN #	DATE	REV	APPR / DATE	ECR/ECN #	DATE	REV	APPR / DATE
	05/22/2017		CLK 05/22/2017				
29124	11/06/2018	A	CLK 11/06/2018				