

SPECIFICATION SHEET

JFW MODEL 75P-154

RELAY PROGRAMMABLE ATTENUATOR

JFW Industries, Inc.
Phone: 317-887-1340
sales@jfwindustries.com
www.jfwindustries.com

Frequency Range	DC-1000 MHz
Impedance	75 Ohms nominal
Attenuation Range	0-63.75 dB in 0.25 dB steps
Attenuation Steps	0.25, 0.5, 1, 2, 4, 8, 16, and 32 dB
VSWR	1.4:1 maximum
Attenuation Accuracy	0.25 dB ± 0.05 dB 0.5, 1, and 2 dB ± 0.1 dB 4 and 8 dB ± 0.2 dB 16 dB ± 0.3 dB 32 dB ± 0.4 dB Accumulated Error ± 0.5 dB or 1.5% (whichever is greater)
Insertion Loss	2.2 dB maximum 0.75 dB typical at 500 MHz 1.50 dB typical at 1000 MHz
RF Input Power	0.5 Watts average
Switching Speed	10 milliseconds
DC Supply	+12 Vdc @ 30 mA per relay (8 relays total)
Control (8 lines)	TTL Low for Thru Path TTL High for Attenuation
DC Connector	3M #3793-5303
RF Connector	BNC, F, N, or TNC female
Operating Temperature Range	0°C to +70°C
Physical Size	See outline drawing 092-2213

ECR/ECN #	DATE	REV	APPR / DATE	ECR/ECN #	DATE	REV	APPR / DATE
	03/04/2004		TRS 03/04/2004				
13974	03/20/2007	A	TRS 03/20/2007				