

SPECIFICATION SHEET
JFW MODEL 75FHC-XXX-10
FIXED ATTENUATOR

JFW Industries, Inc.
 Phone: 317-887-1340
 sales@jfwindustries.com
 www.jfwindustries.com

Frequency Range	DC-3000 MHz
Impedance	75 Ohms nominal
Attenuation Values	3, 6, 9, 10, 12, 20, 25 and 30dB
VSWR	1.2:1 DC-1000 MHz 1.3:1 1000-2000 MHz 1.5:1 2000-3000 MHz
Attenuation Accuracy	3dB: ± 0.5dB 6dB: ± 0.6dB 9-30dB: ± 0.5dB DC-1000 MHz ± 1.0dB 1000-3000 MHz
RF Input Power	10 Watts average @ +25°C Derate to 5 Watts @ +70°C
Peak Power	1000 Watts
RF Connector	BNC or N
Physical Size	See outline drawing 092-1878

ECR/ECN #	DATE	REV	APPR / DATE	ECR/ECN #	DATE	REV	APPR / DATE
	10/24/2008		SMR 10/24/2008	28457	01/25/2018	C	CLK 01/25/2018
21088	12/29/2011	A	CLK 12/29/2011	28825	06/26/2018	D	CLK 06/26/2018
26685	05/26/2016	B	TRS 05/26/2016				