

SPECIFICATION SHEET

JFW MODEL 50PA-201-XX

PROGRAMMABLE ATTENUATOR ASSEMBLY

JFW Industries, Inc.
Phone: 317-887-1340
sales@jfwindustries.com
www.jfwindustries.com

| | |
|------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Frequency Range | 30-3000 MHz |
| Attenuation Range | 0-95 dB in 1 dB steps |
| Configuration | Individually controlled solid-state programmable attenuators. Number of attenuators can be selected from 9 to 16 attenuators. |
| Enclosure Type | 19 inch rack mount (2RU high for 9-16 attenuators w/ SMA female) (3RU high for 9-12 attenuators w/ N female) (4RU high for 13-16 attenuators w/ N female) |
| Impedance | 50 Ohms nominal |
| Startup/Default States (configurable) | Attenuators to 95dB at startup (see ATTEN command) DHCP enabled (see NET command) 4 Ethernet users (see NET command) Prompts off (see PROMPT command) All of these default settings can be changed by user. Unit can be configured for up to 12 Ethernet users. |
| VSWR | 2.0:1 maximum 30-700 MHz 1.6:1 maximum 700-3000 MHz |
| Attenuation Accuracy | ± 0.50 dB 1-7 dB ± 1.00 dB 8-11 dB ± 1.25 or 3% 12-95 dB (whichever is greater) (guaranteed monotonic) |
| Insertion Loss | 5.5 dB maximum 5.0 dB typical |
| RF Input Power | +27 dBm average +33 dBm no damage |
| Switching Speed | 4 microseconds typical (after command is received and processed) (3 milliseconds typical processing time) |
| Manual Control | 20-Button Keypad and LCD display (IP Address configurable via keypad) (Net mask configurable via keypad) (Gateway configurable via keypad) (Baud rate configurable via keypad) |
| Remote Control | Ethernet (DHCP, TCP/IP, 10/100, up to 12 users) RS-232 (up to 115200 Baud) |

--CONTINUED--

SPECIFICATION SHEET

JFW MODEL 50PA-201-XX

PROGRAMMABLE ATTENUATOR ASSEMBLY

JFW Industries, Inc.
Phone: 317-887-1340
sales@jfwindustries.com
www.jfwindustries.com

Remote Commands

Attenuator Control Commands:

Atten, Set Attenuator, Read Attenuator, Set All Attenuators, Read All Attenuators, Read All Extended, Fade Attenuator, Variable Attenuator Handover, Block, Set Block, Read Block, Read All Blocks, Fade Block, Variable Block Handover

System Commands:

Help, Identification, Store, Recall, Pause, Net, Serial, Close, Disconnect, MOTD, Date, Message, Restrict, IDENT, Name, Show Users, Reboot, Uptime, Prompt

RF Connector

N or SMA female

Operating Temperature Range

0°C to +50°C

AC Supply

100-240 VAC @ 47-63 Hz

Outline Drawing Numbers

092-8343 (SMA female, 9-16 attenuators)
092-8383 (N female, 9-12 attenuators)
092-8384 (N female, 13-16 attenuators)
092-9176 (N/SMA, 12 attenuators)

Example Model Numbers

50PA-201-09 SMA (9 attenuator)
50PA-201-10 SMA (10 attenuators)
50PA-201-11 SMA (11 attenuators)
50PA-201-12 SMA (12 attenuators)
50PA-201-13 SMA (13 attenuators)
50PA-201-14 SMA (14 attenuators)
50PA-201-15 SMA (15 attenuators)
50PA-201-16 SMA (16 attenuators)
50PA-201-09 N (9 attenuator)
50PA-201-10 N (10 attenuators)
50PA-201-11 N (11 attenuators)
50PA-201-12 N (12 attenuators)
50PA-201-13 N (13 attenuators)
50PA-201-14 N (14 attenuators)
50PA-201-15 N (15 attenuators)
50PA-201-16 N (16 attenuators)

| ECR/ECN # | DATE | REV | APPR / DATE | ECR/ECN # | DATE | REV | APPR / DATE |
|-----------|------------|-----|----------------|-----------|------------|-----|----------------|
| | 07/28/2015 | | TRS 07/28/2015 | 29029 | 09/21/2018 | C | TRS 09/21/2018 |
| 25640 | 08/10/2016 | A | TRS 08/10/2015 | | | | |
| 28159 | 10/05/2017 | B | CLK 10/05/2017 | | | | |