




SPECIFICATIONS

Frequency Range:

Input: 100 - 2500 MHz

Output: 200 - 5000 MHz

Input Power Nominal: 0 dBm

Output Power: 0 ± 2 dBm

Control Voltage $I = 70$ mA: +12 Vdc Typ

Spurious¹:

F1: 18 dBc

F3: 25 dBc

Notes:

1. With respect to F2

PORT CONFIGURATION

Input: 1

Output: 2

Ground: Housing

DC Pins: 12 Vdc @ 70 mA

PULSAR MICROWAVE CORPORATION

PULSAR MICROWAVE CORPORATION
48 INDUSTRIAL WEST, CLIFTON NJ 07012
TEL: 973-779-6262 FAX: 973-779-2727
WWW.PULSARMICROWAVE.COM

DESCRIPTION :

Active Doubler

MODEL NO. :

FXG-02-410F

DIMENSIONS ARE IN INCHES

DECIMAL TOLERANCE:

2 PLACE $\pm .02$

3 PLACE $\pm .010$

SIZE
A

CAGE CODE :
0HR85

REV CODE :

170201

SCALE : N / A

ALL SPECIFICATIONS ARE SUBJECT TO
CHANGE WITHOUT NOTICE AT ANY TIME

SHEET 1 OF 1