

# Ultra-Small Ceramic Power Splitter/Combiner

## QCN-13D+

2 Way-90° 50Ω 675 to 1300 MHz



CASE STYLE: FV1206-1

### Maximum Ratings

Operating Temperature	-55°C to 100°C
Storage Temperature	-55°C to 100°C
Power Input (as a splitter)	15W* max.

\* Derate linearly to 7W at 100°C ambient.  
Permanent damage may occur if any of these limits are exceeded.

### Pin Connections

SUM PORT	1
PORT 1 (0°)	4
PORT 2 (+90°)	6
GROUND	2,5
50 OHM TERM EXTERNAL	3

### Features

- low insertion loss, 0.4 dB typ.
- high isolation, 19 dB typ.
- wrap-around terminal for excellent solderability
- ultra small, 0.12"X0.06"X0.035"

### Applications

- balanced amplifiers
- modulators
- GSM
- defense communication
- WiMax 700
- GPS civilian

**+RoHS Compliant**  
The +Suffix identifies RoHS Compliance. See our web site for RoHS Compliance methodologies and qualifications

Available Tape and Reel at no extra cost  
Reel Size Devices/Reel  
7" 20, 50, 100, 200, 500, 1000, 3000

### Electrical Specifications

FREQ. RANGE (MHz)	ISOLATION (dB)		INSERTION LOSS (dB) Avg. of Coupled Outputs ABOVE 3 dB		PHASE UNBALANCE (Degrees)		AMPLITUDE UNBALANCE (dB)		VSWR (:1)
	Typ.	Min.	Typ.	Max.	Typ.	Max.	Typ.	Max.	
$f_L$ - $f_U$									Typ.
675-1300	20	14	0.4	0.9	1.0	8.0	1.0	1.3	1.2
675-820	19	15	0.3	0.5	1.0	4.0	0.7	1.0	1.25
820-900	19	16	0.3	0.5	0.5	3.0	0.6	1.0	1.2
900-1000	19	16	0.4	0.6	1.0	3.0	0.8	1.2	1.2
1000-1200	17	14	0.4	0.6	3.0	5.0	0.8	1.2	1.2
1200-1300	15	13	0.5	0.8	5.0	7.0	0.5	0.9	1.25


1. For applications requiring DC voltage to be applied to the RF ports. DC resistance to ground is 100 Mohms min.

### Typical Performance Data

Frequency (MHz)	Total Loss <sup>1</sup> (dB)		Amplitude Unbalance (dB)	Isolation (dB)	Phase Unbalance (deg.)	VSWR S	VSWR 1	VSWR 2
	S-1	S-2						
675.00	3.57	3.02	0.55	19.07	88.87	1.27	1.22	1.26
698.00	3.47	3.11	0.36	19.18	89.01	1.27	1.21	1.26
750.00	3.27	3.30	0.02	19.44	89.31	1.26	1.18	1.24
806.00	3.10	3.47	0.37	19.74	89.65	1.25	1.15	1.22
824.00	3.06	3.52	0.46	19.81	89.77	1.25	1.15	1.22
875.00	2.95	3.65	0.69	20.01	90.06	1.25	1.13	1.21
894.00	2.93	3.69	0.76	20.08	90.17	1.25	1.12	1.20
900.00	2.92	3.70	0.78	20.09	90.19	1.25	1.12	1.20
960.00	2.85	3.80	0.95	20.20	90.57	1.27	1.11	1.19
1000.00	2.84	3.85	1.01	20.22	90.81	1.28	1.11	1.18
1150.00	3.01	3.83	0.82	19.36	91.94	1.36	1.17	1.18
1210.00	3.20	3.74	0.54	18.64	92.48	1.42	1.21	1.19
1225.00	3.26	3.71	0.44	18.37	92.65	1.44	1.22	1.19
1310.00	3.79	3.46	0.32	16.71	93.90	1.56	1.30	1.23

1. Total Loss = Insertion Loss + 3dB splitter loss.


### Outline Drawing



### Outline Dimensions (inch/mm)

A	B	C	D	E	F
.126	.063	.035	.024	.022	.011
3.20	1.60	0.89	0.61	0.56	0.28
G	H	J	K	wt	
.039	.024	.042	.123	grams	
0.99	0.61	1.07	3.12	.020	

### Demo Board MCL P/N: TB-255+ Suggested PCB Layout (PL-131)






NOTES: 1. TRACE WIDTH IS SHOWN FOR ROGERS RO4350B WITH DIELECTRIC THICKNESS 0.020" ± 0.0015"; COPPER: 1/2 OZ. EACH SIDE. FOR OTHER MATERIALS TRACE WIDTH MAY NEED TO BE MODIFIED.

2. BOTTOM SIDE OF THE PCB IS CONTINUOUS GROUND PLANE.
- DENOTES PCB COPPER LAYOUT WITH SMOBC (SOLDER MASK OVER BARE COPPER)
  - DENOTES COPPER LAND PATTERN FREE OF SOLDER MASK

#### Notes

- A. Performance and quality attributes and conditions not expressly stated in this specification document are intended to be excluded and do not form a part of this specification document.
- B. Electrical specifications and performance data contained in this specification document are based on Mini-Circuit's applicable established test performance criteria and measurement instructions.
- C. The parts covered by this specification document are subject to Mini-Circuit's standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuit's website at [www.minicircuits.com/MCLStore/terms.jsp](http://www.minicircuits.com/MCLStore/terms.jsp)



### electrical schematic (Note 1)

