

Power Splitter/Combiner

SCPJ-2-9+

2 Way-180° 50Ω

200 to 900 MHz



CASE STYLE: YY161


Maximum Ratings

Operating Temperature	-40°C to 85°C
Storage Temperature	-55°C to 100°C
Power Input (as a splitter)	1W max.
Internal Dissipation	0.125W max.
Permanent damage may occur if any of these limits are exceeded.	

Pin Connections

SUM PORT	1
PORT 1	5
PORT 2	6
GROUND	2,3,4,7,8

Outline Drawing




Outline Dimensions (inch/mm)

A	B	C	D	E	F	G
0.75	0.38	0.28	0.01	0.05	0.02	0.2
19.05	9.65	7.11	0.25	1.27	0.51	5.08

H	J	K	M	N	P	wt
0.075	0.6	0.45	0.47	0.1	0.15	grams
1.91	15.24	11.43	11.94	2.54	3.81	1.60

Demo Board MCL P/N: TB-50+ Suggested PCB Layout (PL-060)



- NOTES: 1. TRACE WIDTH IS SHOWN FOR ROGERS RO4350B WITH DIELECTRIC THICKNESS .030" ± .002". COPPER: 1/2 OZ. EACH SIDE. FOR OTHER MATERIALS TRACE WIDTH MAY NEED TO BE MODIFIED.
2. BOTTOM SIDE OF THE PCB IS CONTINUOUS GROUND PLANE.
- DENOTES PCB COPPER LAYOUT WITH SMOBC (SOLDER MASK OVER BARE COPPER)
- DENOTES COPPER LAND PATTERN FREE OF SOLDER MASK

Notes

- A. Performance and quality attributes and conditions not expressly stated in this specification document are intended to be excluded and do not form a part of this specification document.
- B. Electrical specifications and performance data contained in this specification document are based on Mini-Circuit's applicable established test performance criteria and measurement instructions.
- C. The parts covered by this specification document are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCLStore/terms.jsp

Features

- wideband, 200 to 900 MHz
- good isolation, 24 dB typ.
- excellent amplitude unbalance, 0.4 dB typ.

Applications

- VHF/UHF
- cellular
- communication systems




Electrical Specifications

FREQ. RANGE (MHz)	ISOLATION (dB)	INSERTION LOSS (dB) ABOVE 3 dB	PHASE UNBALANCE (Degrees)	AMPLITUDE UNBALANCE (dB)
f_L - f_U	Typ. Min.	Typ. Max.	Max.	Max.
200-900	24 17	1.0 1.8	6	0.7

Typical Performance Data

Frequency (MHz)	Total Loss ¹ (dB)	Amplitude Unbalance (dB)	Isolation (dB)	Phase Unbalance (deg.)	VSWR S	VSWR 1	VSWR 2
	S-1 S-2						
201.54	4.06 3.65	0.41	22.58	183.33	1.42	1.27	1.13
265.38	3.90 3.60	0.29	22.25	181.67	1.37	1.21	1.14
297.31	4.03 3.71	0.33	22.26	180.97	1.36	1.19	1.14
361.15	3.91 3.68	0.23	22.27	179.90	1.33	1.17	1.15
393.08	3.96 3.73	0.23	22.30	179.67	1.29	1.17	1.14
463.64	4.01 3.83	0.18	22.66	178.81	1.28	1.18	1.15
502.27	3.91 3.79	0.13	23.00	178.58	1.23	1.19	1.14
540.91	3.98 3.84	0.14	23.36	178.37	1.24	1.20	1.15
618.18	4.03 3.96	0.07	24.25	181.90	1.20	1.20	1.15
695.45	4.05 4.06	0.00	25.27	181.65	1.10	1.20	1.17
734.09	4.08 4.05	0.04	25.64	181.51	1.11	1.20	1.20
811.36	4.15 4.23	0.08	24.90	181.15	1.08	1.17	1.25
850.00	4.26 4.24	0.02	23.66	179.95	1.05	1.16	1.31
913.64	4.34 4.46	0.12	21.20	180.00	1.16	1.13	1.37

1. Total Loss = Insertion Loss + 3dB splitter loss.



electrical schematic

