

Surface Mount Directional Coupler

75Ω, 12dB Coupling, 5 to 1200 MHz


Maximum Ratings

Operating Temperature	-40°C to 85°C
Storage Temperature	-55°C to 100°C
Permanent damage may occur if any of these limits are exceeded.	


Pin Connections

INPUT	3
OUTPUT	4
COUPLED	1
GROUND	2
ISOLATE (DO NOT USE)	6

Outline Drawing




PCB Land Pattern



Outline Dimensions (inch/mm)

A	B	C	D	E	F
.150	.150	.150	.050	.030	.025
3.81	3.81	3.81	1.27	0.76	0.64
G	H	J	K		wt
.028	.050	.160	.030		grams
0.71	1.27	4.06	0.76		0.10

Demo Board MCL P/N: TB-279 Suggested PCB Layout (PL-151)



- NOTES: 1. TRACE WIDTH IS SHOWN FOR ROGERS RO4350B WITH DIELECTRIC THICKNESS 0.030" ± 0.002"; COPPER: 1/2 OZ. EACH SIDE. FOR OTHER MATERIALS TRACE WIDTH MAY NEED TO BE MODIFIED.
2. BOTTOM SIDE OF THE PCB IS CONTINUOUS GROUND PLANE.
-  DENOTES PCB COPPER LAYOUT WITH SMOBC (SOLDER MASK OVER BARE COPPER)
-  DENOTES COPPER LAND PATTERN FREE OF SOLDER MASK

Features

- very flat coupling
- very broadband, multi octave
- temperature stable, LTCC base
- all welded construction
- leads attached for better solderability
- micro miniature coupler
- aqueous washable
- protected by US Patents 6,140,887 & 6,784,521

Applications




- CATV
- wire-line broadband access

Electrical Specifications


FREQ. (MHz)	COUPLING (dB)		MAINLINE LOSS ¹ (dB)		DIRECTIVITY (dB)		VSWR (:1)	POWER INPUT (W)
	Nom.	Max. Flatness	Typ.	Max.	Typ.	Min.		
5-1200	12±0.5	±0.6						
5-50			1.1	1.8	19	17	1.3	0.5
50-500			1.1	1.4	18	15	1.3	1.0
500-1000			1.2	1.6	17	10	1.3	1.0
1000-1200			1.3	1.9	13	8	1.3	1.0

Typical Performance Data

Frequency (MHz)	Mainline Loss (dB) In-Out		Coupling (dB) In-Cpl	Directivity (dB)	Return Loss (dB)		
					In	Out	Cpl
5.00	1.11	11.92	19.03	18.05	22.21	20.18	
50.00	1.04	11.93	19.50	19.49	26.11	21.12	
180.00	1.04	11.98	18.67	19.58	26.61	18.80	
340.00	1.01	11.99	18.30	20.15	23.62	15.48	
500.00	1.05	12.00	16.68	20.32	21.63	12.88	
700.00	1.18	12.15	15.13	18.84	19.39	10.88	
870.00	1.28	12.24	13.39	19.80	18.65	9.82	
1000.00	1.26	12.29	12.40	21.00	18.94	9.27	
1100.00	1.32	12.34	11.84	22.53	19.49	8.90	
1200.00	1.38	12.41	11.54	24.40	20.24	8.59	



Electrical Schematic



* ELECTRICAL SCHEMATIC IS FOR DIRECTIONAL COUPLER WITH INTERNAL TRANSFORMER(S) THAT ROUTES DC FROM RF PORTS TO GROUND.


Notes

- A. Performance and quality attributes and conditions not expressly stated in this specification document are intended to be excluded and do not form a part of this specification document.
- B. Electrical specifications and performance data contained in this specification document are based on Mini-Circuits' applicable established test performance criteria and measurement instructions.
- C. The parts covered by this specification document are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCLStore/terms.jsp



www.minicircuits.com P.O. Box 350166, Brooklyn, NY 11235-0003 (718) 934-4500 sales@minicircuits.com

DBTC-12-4-75X+



CASE STYLE: AT1667-1

+RoHS Compliant

The +Suffix identifies RoHS Compliance. See our web site for RoHS Compliance methodologies and qualifications

Reel Size	Devices/Reel
7"	20, 50, 100, 200
13"	500, 1000, 2000

REV. A
M151107
ED-12343A/1
DBTC-12-4-75X+
RS/CP/AM
151222