

Product Overview

The QPD0060 is a wide band over-molded DFN discrete power amplifier. The device is a single stage unmatched power amplifier transistor.

The QPD0060 can be used in Doherty architecture for the final stage of a base station amplifier for small cell, microcell, and active antenna systems. The QPD0060 can also be used as a driver in a macrocell base station power amplifier.

The wide bandwidth of the QPD0060 makes it suitable for many different applications from DC to 2.7 GHz. QPD0060 can deliver P_{SAT} of 89.1 W at +48 V operation at 2.1 GHz.

Lead-free and RoHS compliant.



6 Pin 7.2 x 6.6 mm DFN Package


Key Features

- Operating Frequency Range: DC to 2.7 GHz
- Operating Drain Voltage: +48 V
- Maximum Output Power (P_{SAT}): 89.1 W ⁽¹⁾
- Maximum Drain Efficiency: 74.7% ⁽¹⁾
- Efficiency-Tuned P3dB Gain: 21.5 dB ⁽¹⁾
- Surface Mount Plastic Package

Notes:

1. Load pull performance at 2.1 GHz.

Functional Block Diagram



Applications

- W-CDMA / LTE
- Macrocell Base Station Driver
- Microcell Base Station
- Small Cell Final Stage
- Active Antenna
- General Purpose Applications

Ordering Information

Part Number	Description
QPD0060S2	Sample – 2 Pieces
QPD0060SB	Sample Box – 5 Pieces
QPD0060SR	Short Reel – 100 Pieces
QPD0060TR7	7" Reel – 500 pieces
QPD0060PCB4B01	1.8 – 2.2 GHz Evaluation Board
QPD0060EVB01	762 – 944 MHz Evaluation Board
QPD0060EVB02	136 – 944 MHz Evaluation Board

Absolute Maximum Ratings

Parameter	Rating
Breakdown Voltage (BV_{DG})	+165 V
Gate Voltage Range (V_G)	-7 to +2 V
Drain Voltage (V_D)	+55 V
Peak RF Input Power	38 dBm
VSWR Mismatch, P1dB Pulse (20% Duty Cycle, 100 μ s Width), $T = +25^\circ\text{C}$	10:1

Exceeding any one or a combination of the Absolute Maximum Rating conditions may cause permanent damage to the device. Extended application of Absolute Maximum Rating conditions to the device may reduce device reliability.

Recommended Operating Conditions

Parameter	Min	Typ	Max	Units
Gate Voltage (V_G)		-2.7		V
Drain Voltage (V_D)		+48		V
Quiescent Current (I_{DQ})		130		mA

Electrical specifications are measured at specified test conditions. Specifications are not guaranteed over all recommended operating conditions.

Electrical Specifications

Parameter	Conditions	Min	Typ	Max	Units
Operational Frequency Range		1800		2200	MHz
Quiescent Current (I_{DQ})			130		mA
Gain	3 dB Compression	14.7	16.4		dB
Power (P_{SAT})	3 dB Compression	48.1	49.8		dBm
Drain Efficiency	3 dB Compression	60.0	69.2		%

Test conditions unless otherwise noted: $V_D = +48\text{ V}$, $I_{DQ} = 130\text{ mA}$, $T = +25^\circ\text{C}$, Pulse signal (10% Duty Cycle, 100 μ s Width) at 2010-2200 MHz on a Class AB single-ended reference design fixture tuned for 1.8-2.2 GHz.


Thermal Information

Parameter	Conditions	Values	Units
Doherty Thermal Resistance, Peak IR Surface Temperature at Average Power (θ_{JC}) ^{(1) (2)}	$T_{CASE} = +105^\circ\text{C}$, $T_{CH} = 121^\circ\text{C}$ CW: $P_{DISS} = 11.9\text{ W}$, $P_{OUT} = 17.9\text{ W}$	1.3	$^\circ\text{C/W}$
Device Thermal Resistance, Peak IR Surface Temperature at Average Power (θ_{JC})	$T_{CASE} = +105^\circ\text{C}$, $T_{CH} = 142^\circ\text{C}$ CW: $P_{DISS} = 21.4\text{ W}$, $P_{OUT} = 5\text{ W}$	1.7	$^\circ\text{C/W}$

Notes:

1. Based on expected carrier amplifier efficiency of Doherty.
2. P_{OUT} assumes 20% peaking amplifier contribution of total average Doherty rated power.
3. Thermal resistance is measured to package backside.
4. Refer to the following document: [GaN Device Channel Temperature, Thermal Resistance, and Reliability Estimates](#)







QPD0060PCB4B01 Layout – 1800 – 2200 MHz Reference Design



QPD0060PCB4B01 Bill of Materials





Reference Des.	Value	Description	Manufacturer	Part Number
C1	1.6 pF	Capacitor, 1.6 pF, ± 0.05 pF, 250 V, HI-Q, 0603	ATC	600S1R6AT250XT
C2, C3	3 pF	Capacitor, 3 pF, ± 0.1 pF, 250 V, HI-Q, 0603	ATC	600S3R0BT250XT
C4, C6, C9	20 pF	Capacitor, 20 pF, $\pm 1\%$, 250 V, HI-Q, 0603	ATC	600S200FT250XT
C5, C7, C8	10 μ F	Capacitor, 10 μ F, $\pm 20\%$, 100 V, X7S, 2220	TDK	C5750X7S2A106M230KB
C10	100 μ F	Capacitor, 100 μ F, $\pm 20\%$, 100 V, Electrolytic	Panasonic	EEV-TG2A101M
R1	3 Ω	Resistor, 3 Ω , $\pm 5\%$, 0.1 W, 0603	Vishay	CRCW06033R00FKEAC
R2	220 Ω	Resistor, 220 Ω , $\pm 5\%$, 0.1 W, 0603, Lead Free	KOA Speer	RK73B1JTTD221J
R3	10 Ω	Resistor, 10 Ω , 0603, RoHS	Kamaya	RMC1/16K10R0FTP

QPD0060PCB4B01 Performance Plots




Test conditions unless otherwise noted: $V_D = +48 \text{ V}$, $I_{DQ} = 150 \text{ mA}$, $T = +25^\circ\text{C}$, on a 1.8 – 2.2 GHz reference design fixture.

QPD0060PCB4B01 Performance Plots



Test conditions unless otherwise noted: $V_D = +48$ V, $I_{DQ} = 150$ mA, $T = +25^\circ\text{C}$, on a 1.8 – 2.2 GHz reference design fixture.

QPD0060EVB01 Layout – 762 – 944 MHz Reference Design







Note: PCB material is RO4350B, 20 mil thick substrate, 1 oz. copper each side.

QPD0060EVB01 Bill of Materials


Reference Des.	Value	Description	Manufacturer	Part Number
C1, C2, C15, C18	8.2 pF	Capacitor, 8.2 pF, ± 0.1 pF, 250 V, RF NPO	ATC	600S8R2BT250XT
C3, C19	3.3 pF	Capacitor, 3.3 pF, ± 0.1 pF, 250 V, RF NPO	ATC	600S3R3BT250XT
C4	22 pF	Capacitor, 22 pF, $\pm 5\%$, 250 V, RF NPO	ATC	600S220JT250XT
C5, C6	1 μ F	Capacitor, 1 μ F, $\pm 10\%$, 100 V, X7S, 0805	TDK	CGA4J3X7S2A105K
C7	10 μ F	Capacitor, 10 μ F, $\pm 10\%$, 100 V, X7S, 2220	TDK	C5750X7S2A106K230KB
C8, C9	0.1 μ F	Capacitor, 0.1 μ F, $\pm 10\%$, 100 V, X7R, 0603	Murata	GRM188R72A104KA35D
C10, C11, C12	100 pF	Capacitor, 100 pF, $\pm 5\%$, 250 V, RF C0G	TDK	C1608C0G2E101JT080AA
C13, C14	15 pF	Capacitor, 15 pF, $\pm 5\%$, 250 V, RF NPO	ATC	600S150JT250XT
C16	100 μ F	Capacitor, 100 μ F, $\pm 20\%$, 100 V, ALUM, 12.5x12.5 mm	BC Components	MAL215099907E3
C20	47 pF	Capacitor, 47 pF, $\pm 5\%$, 250 V, RF NPO	ATC	600S470JT250XT
L1	68 nH	Inductor, 68 nH, $\pm 10\%$, 0805 W/W	Coilcraft	0805CS-680XK
L2	47 nH	Inductor, 47 nH, $\pm 5\%$, 1515	Coilcraft	1515SQ-47NJ
R1, R2, R3, R4, R5	10 Ω	Resistor, 10 Ω , $\pm 5\%$, 0603, Thick Film	KOA Speer	RK73B1JT250XT
R6	1 k Ω	Resistor, 1000 Ω , $\pm 1\%$, 0603, Thick Film	Cal-Chip	RM06F1001CT
R7, R8	5.1 Ω	Resistor, 5.1 Ω , $\pm 1\%$, 0805, Thick Film	Vishay	CRCW08055R10FKEA
R9	120 Ω	0603 1% Thick Film Resistor	KOA Speer	RK73B1JT250XT

QPD0060EVB01 Performance Plots



Test conditions unless otherwise noted: $V_D = +50$ V, $I_{DQ} = 150$ mA, $T = +25^\circ\text{C}$, Pulsed (10% Duty Cycle, 100 μs Width) on a 762 – 944 MHz reference design fixture.

QPD0060EVB02 Layout – 136 – 944 MHz Reference Design







Note: PCB material is RO4350B, 20 mil thick substrate, 1 oz. copper each side.

QPD0060EVB02 Bill of Materials

Reference Des.	Value	Description	Manufacturer	Part Number
C1	22 pF	Capacitor, 22 pF, $\pm 5\%$, 250 V, RF NPO	ATC	600S220JT250XT
C2, C13, C14, C17	240 pF	Capacitor, 240 pF, $\pm 5\%$, 250 V, RF NPO	ATC	600F241JT250XT
C3	3.3 pF	Capacitor, 3.3 pF, ± 0.1 pF, 250 V, RF NPO	ATC	600S3R3BT250XT
C4	8.2 pF	Capacitor, 8.2 pF, $\pm 5\%$, 250 V, RF NPO	ATC	600S8R2JT250XT
C5, C6	1 μ F	Capacitor, 1 μ F, $\pm 10\%$, 100 V, X7S, 0805	TDK	CGA4J3X7S2A105K
C7	10 μ F	Capacitor, 10 μ F, $\pm 10\%$, 100 V, X7S, 2220	TDK	C5750X7S2A106K230KB
C8, C9	0.1 μ F	Capacitor, 0.1 μ F, $\pm 10\%$, 100 V, X7R, 0603	Murata	GRM188R72A104KA35D
C10, C11, C12, C15	100 pF	Capacitor, 100 pF, $\pm 5\%$, 250 V, RF NPO	ATC	600S101JT250XT
C16	100 μ F	Capacitor, 100 μ F, $\pm 20\%$, 100 V, ALUM, 12.5x12.5 mm	BC Components	MAL215099907E3
C18	6.8 pF	Capacitor, 6.8 pF, ± 0.1 pF, 250 V, RF C0G	ATC	600F6R8BT250XT
L1	68 nH	Inductor, 68 nH, $\pm 10\%$, 0805, W/W	Coilcraft	0805CS-680XK
L2	82 nH	Inductor, 82 nH, $\pm 5\%$, 1515	Coilcraft	1515SQ-82NJ
L3	1.8 nH	Inductor, 1.8 nH, $\pm 5\%$, 0603	Coilcraft	0603HP-1N8XJ
R1, R2, R3, R4, R5	10 Ω	Resistor, 10 Ω , $\pm 5\%$, 0603, Thick Film	KOA Speer	RK73B1JTTD100J
R6	27 Ω	Resistor, 27 Ω , $\pm 5\%$, 0603, Thick Film	Panasonic	ERJ-3GEYJ270
R7, R8	5.1 Ω	Resistor, 5.1 Ω , $\pm 1\%$, 0805, Thick Film	Vishay	CRCW08055R10FKEA
R9, R10	240 Ω	Resistor, 240 Ω , $\pm 1\%$, 0603, Thick Film	Samsung	RC1608F241CS
R11	10 Ω	Resistor, 10 Ω , $\pm 5\%$, 0805, Thick Film	KOA Speer	RK73B2ALTD100J
T1	12.5 Ω	Impedance Transformer 50-12.5 Ω	Anaren	XMT0310B5012

QPD0060EVB02 Performance Plots



Test conditions unless otherwise noted: $V_D = +50$ V, $I_{DQ} = 150$ mA, $T = +25^\circ\text{C}$, Pulsed (10% Duty Cycle, 100 μs Width) on a 136 – 944 MHz reference design fixture.

Power-Matched Load Pull Performance

Frequency (MHz)	Source Impedance (Ω)	Load Impedance (Ω)	P3dB (dBm)	Drain Efficiency (%)	G3dB (dB)
1800	2.0 – j6.0	5.7 + j1.4	49.2	61.2	19.9
1900	2.1 – j6.9	5.5 + j0.7	49.2	62.0	19.7
2100	2.9 – j10.3	6.4 + j1.0	49.5	65.7	19.6
2200	4.2 – j13.5	5.0 + j0.1	49.5	65.9	18.7
2600	8.9 + j13.3	4.8 + j0.0	49.0	63.0	18.2

Test conditions unless otherwise noted: $V_D = +48$ V, $I_{DQ} = 150$ mA, $T = +25^\circ\text{C}$, Pulse (10% Duty Cycle, 100 μs Width).



Efficiency-Matched Load Pull Performance

Frequency (MHz)	Source Impedance (Ω)	Load Impedance (Ω)	P3dB (dBm)	Drain Efficiency (%)	G3dB (dB)
1800	2.0 – j6.0	5.4 + j7.3	47.2	74.9	21.9
1900	2.1 – j6.9	5.1 + j5.7	47.7	75.8	22.0
2100	2.9 – j10.3	4.7 + j3.5	48.5	74.7	21.5
2200	4.2 – j13.5	4.7 + j3.5	48.4	73.9	20.9
2600	8.9 + j13.3	3.1 + 2.6	46.6	68.3	20.0

Test conditions unless otherwise noted: $V_D = +48$ V, $I_{DQ} = 150$ mA, $T = +25^\circ\text{C}$, Pulse (10% Duty Cycle, 100 μs Width).




Load Pull Contours

Test Conditions unless otherwise noted: $V_D = +48$ V, $I_{DQ} = 150$ mA, $T = +25^\circ\text{C}$, Pulse (10% Duty Cycle, 100 μs Width).




Load Pull Contours

Test Conditions unless otherwise noted: $V_D = +48\text{ V}$, $I_{DQ} = 150\text{ mA}$, $T = +25^\circ\text{C}$, Pulse (10% Duty Cycle, 100 μs Width).




Package Markings

Marking: Qorvo Logo
Part Number – QPD0060
Date Code – YYWW
Lot Code – MXXX
Serial Number – ZZZ




Package Dimensions



Notes:

1. Dimensions are in millimeters [inches]. Angles are in degrees.
2. Part is overmold encapsulated.
3. Contact plating is NiPdAu. Au thickness is 0.00254 to 0.01501 μm .
4. General tolerance is ± 0.25 .

Pin Configuration and Description




Pin Number	Label	Description
1, 2, 3	RF IN, V_G	RF Input, Gate Bias
4, 5, 6	RF OUT, V_D	RF Output, Drain Bias
7 (Backside Paddle)	RF/DC GND	RF/DC Ground

Bias Procedure

Bias-Up Procedure	Bias-Down Procedure
1. Set V_G to -4 V. 2. Apply $+48$ V to V_D. 3. Slowly adjust V_G until I_D is set to 130 mA. 4. Apply RF.	1. Turn off RF signal. 2. Turn off V_D. 3. Wait two (2) seconds to allow drain capacitor to discharge. 4. Turn off V_G.

Recommended Solder Temperature Profile



Handling Precautions

Parameter	Rating	Standard
ESD – Human Body Model (HBM)	Class 1A	ANSI/ESDA/JEDEC Standard JS-001
ESD – Charged Device Model (CDM)	Class C3	ANSI/ESDA/JEDEC Standard JS-002
MSL – Moisture Sensitivity Level	Level 3	IPC/JEDEC Standard J-STD-020



Solderability

Compatible with lead-free (260°C max. reflow temp.) soldering processes.

Package lead plating is NiPdAu. Au thickness is 0.00254 to 0.01501 µm.

RoHS Compliance

This part is compliant with 2011/65/EU RoHS directive (Restrictions on the Use of Certain Hazardous Substances in Electrical and Electronic Equipment) as amended by Directive 2015/863/EU.

This product also has the following attributes:

- Lead Free
- Halogen Free (Chlorine, Bromine)
- Antimony Free
- TBBP-A (C₁₅H₁₂Br₄O₂) Free
- PFOS Free
- SVHC Free



Contact Information

For the latest specifications, additional product information, worldwide sales and distribution locations:

Web: www.qorvo.com

Tel: 1-844-890-8163

Email: customer.support@qorvo.com

For technical questions and application information:

Email: BTSAApplications@qorvo.com

Important Notice

The information contained herein is believed to be reliable; however, Qorvo makes no warranties regarding the information contained herein and assumes no responsibility or liability whatsoever for the use of the information contained herein. All information contained herein is subject to change without notice. Customers should obtain and verify the latest relevant information before placing orders for Qorvo products. The information contained herein or any use of such information does not grant, explicitly or implicitly, to any party any patent rights, licenses, or any other intellectual property rights, whether with regard to such information itself or anything described by such information. **THIS INFORMATION DOES NOT CONSTITUTE A WARRANTY WITH RESPECT TO THE PRODUCTS DESCRIBED HEREIN, AND QORVO HEREBY DISCLAIMS ANY AND ALL WARRANTIES WITH RESPECT TO SUCH PRODUCTS WHETHER EXPRESS OR IMPLIED BY LAW, COURSE OF DEALING, COURSE OF PERFORMANCE, USAGE OF TRADE OR OTHERWISE, INCLUDING THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.**

Without limiting the generality of the foregoing, Qorvo products are not warranted or authorized for use as critical components in medical, life-saving, or life-sustaining applications, or other applications where a failure would reasonably be expected to cause severe personal injury or death.

Copyright 2018 © Qorvo, Inc. | Qorvo is a registered trademark of Qorvo, Inc.