



RF-LAMBDA

LEADER OF RF BROADBAND SOLUTIONS

RFSP2TR230M300M

Reflective Coaxial SP2T Switch 230 – 300MHz



Features

- Wide Band Operation 230-300MHz
- TTL compatible driver included
- Fast Switching Speed
- Low Insertion Loss and High Isolation

Typical Applications

- Military and Aerospace
- Wireless Infrastructure

Electrical Specifications, TA = +25°C, Vdd = +5V/-28V, TTL = 0 / +5V

Description	PN: RFSP2TR230M300M			
	SP2T Reflective Switch			
	High Power Cold Switching			
Parameters	Min	Typ	Max	Units
Frequency Range	230 - 300			MHz
Insertion Loss		0.4	0.6	dB
Insertion Loss Temperature Coefficient		0.003		dB/°C
Isolation	50	65		dB
Input VSWR		1.2	1.3	:1
Output VSWR		1.2	1.3	:1
Input Peak Power (50% duty cycle, 125us pulse width)			125	W
DC Power Dissipation		2		W
0.1dB Compression Point (Po.1dB)		51		dBm
IIP3		50		dBm
Switching Speed			1.2	us
Weight	5.29			ounces
Impedance	50			Ω
Bias Current(+5V / -28V)	250/50			mA
Input / Output Connectors	N - Female			
Finish	Nickel Plated			
Material	Aluminum			
Sealing	Hermetically Sealed (Optional)			

Reflective Coaxial Single Pole Double Throw Switch 230 – 300MHz



RF-LAMBDA

LEADER OF RF BROADBAND SOLUTIONS

RFSP2TR230M300M

Absolute Maximum Ratings

Biasing	+5V±10%/-28V±10%
TTL Control Voltage	0~0.8V / 2.8~5V

Note: TTL pins cannot be connected to the negative voltage otherwise the internal driver will be damaged.

Ordering Information

Part No.	ECCN	Description
RFSP2TR230M300M	EAR99	SP2T 230-300MHz PIN Diode Switch

Environmental Specifications and Test Standards

Parameter	Standard	Description
Operational Temperature	MIL-STD-39016	-45°C~+85°C
Storage Temperature		-55°C~+125°C
Thermal Shock		1 Hour@ -45°C → 1 Hour @ +85°C (5 Cycles)
Random Vibration		Acceleration Spectral Density 6 (m/s) Total 92.6 RMS
Electrical & Temperature Burn In		Temperature +85°C for 72 Hours
Shock		1. Weight >20g, 50g half sine wave for 11ms, Speed variation 3.44m/s 2. Weight <=20g, 100g Half sine wave for 6ms, Speed variation 3.75m/s 3. Total 18 times (6 directions, 3 repetitions per direction).
Altitude	MIL-STD-883	Standard: 30,000 Ft (Epoxy Sealed Controlled Environment) Optional: Hermetically Sealed (60,000 ft. 1.0 PSI min)
Hermetically Sealed (Optional)		MIL-STD-883 (For Hermetically Sealed Units)

Reflective Coaxial Single Pole Double Throw Switch 230 – 300MHz



RF-LAMBDA


LEADER OF RF BROADBAND SOLUTIONS

RFSP2TR230M300M


Reflective Coaxial Single Pole Double Throw Switch 230 – 300MHz

Typical Performance Plots


Insertion Loss @+25°C




Input VSWR @+25°C




Output VSWR @+25°C




Isolation @+25°C




Insertion Loss @-45°C




Input VSWR @-45°C



Output VSWR @-45°C



Isolation @-45°C






RF-LAMBDA

LEADER OF RF BROADBAND SOLUTIONS


RFSP2TR230M300M

Reflective Coaxial Single Pole Double Throw Switch 230 – 300MHz


Insertion Loss @+85°C




Input VSWR @+85°C




Output VSWR @+85°C




Isolation @+85°C



Switching Speed



Switching Speed






Outline Drawing:

All Dimensions in mm [inches]

[X207]



Truth Table

Control Input TTL		Signal Path State
C2	C1	
0	0	OFF
0	1	J0-J1
1	0	J0-J2
1	1	Not Used
Control Pin Customization available upon request		



Important Notice

The information contained herein is believed to be reliable. RF-Lambda makes no warranties regarding the information contained herein. RF-Lambda assumes no responsibility or liability whatsoever for any of the information contained herein. RF-Lambda assumes no responsibility or liability whatsoever for the use of the information contained herein. The information contained herein is provided "AS IS, WHERE IS" and with all faults, and the entire risk associated with such information is entirely with the user. All information contained herein is subject to change without notice. Customers should obtain and verify the latest relevant information before placing orders for RF-Lambda products. The information contained herein or any use of such information does not grant, explicitly or implicitly, to any party any patent rights, licenses, or any other intellectual property rights, whether with regard to such information itself or anything described by such information. RF-Lambda products are not warranted or authorized for use as critical components in medical, life-saving, or life sustaining applications, or other applications where a failure would reasonably be expected to cause severe personal injury or death.

Reflective Coaxial Single Pole Double Throw Switch 230 – 300MHz