




RF-LAMBDA

LEADER OF RF BROADBAND SOLUTIONS

RFSP8TA5M43G

Absorptive Coaxial SP8T Switch 0.5 - 43.5GHz



Features

- Ultra Wide Band Operation 0.5-43.5GHz
- TTL compatible driver included
- Fast Switching Speed
- Low Insertion Loss and High Isolation
- Customization available upon request

Typical Applications

- Wireless Infrastructure
- Military and Aerospace
- Test and Measurement

Electrical Specifications, TA = +25° C, Vdd = +5V/-5V, TTL = 0 / +5V

Description	PN: RFSP8TA5M43G									
	SP8T Absorptive Switch									
	Low Power Cold Switching									
	Min	Typ	Max	Min	Typ	Max	Min	Typ	Max	Units
Parameter										
Frequency Range	0.5		8	8		26.5	26.5		43.5	GHz
Insertion Loss		4.2	4.5		6.5	7		7.5	8.5	dB
Insertion Loss Temperature Coefficient		0.003			0.003			0.003		dB/°C
Isolation	60	70		50	58		48	55		dB
Input VSWR		2	3		1.9	3		1.8	2.5	:1
Output VSWR		2	3		1.9	3		1.8	2.5	:1
RF Input power (CW)			23			23			23	dBm
DC Power Dissipation		0.8			0.8			0.8		W
0.1dB Compression Point(Po.1dB)		23			23			23		dBm
IIP3		55			55			50		dBm
Switching Speed		50	100		50	100		50	100	ns
Weight	1.41									ounces
Impedance	50									Ω
Bias Current (+5V/-5V)	200/50									mA
Input / Output Connectors	2.92mm - Female									
Finish	Gold Plated									
Material	Aluminum									
Sealing	Hermetically Sealed (Optional)									

Absorptive Coaxial Single Pole Eight Throw Switch 0.5 - 43.5GHz



Absolute Maximum Ratings

Biasing Voltage	+5V±10%/-5V±10%
TTL Control Voltage	0~ 0.8V / 2.8 ~ 5V

Note: TTL pins cannot be connected to the negative voltage otherwise the internal driver will be damaged.

Ordering Information

Part No.	ECCN	Description
RFSP8TA5M43G	EAR99	SP8T 0.5-43.5PIN Diode Switch


Environmental Specifications and Test Standards

Parameter	Standard	Description
Operational Temperature	MIL-STD-39016	-45°C~+85°C (Case Temperature)
Storage Temperature		-50°C~+125°C
Thermal Shock		1 Hour@ -45°C → 1 Hour @ +85°C (5 Cycles)
Random Vibration		Acceleration Spectral Density 6 (m/s) Total 92.6 RMS
Electrical & Temperature Burn In		Temperature +85°C for 72 Hours
Shock		1. Weight >20g, 50g half sine wave for 11ms, Speed variation 3.44m/s 2. Weight <=20g, 100g Half sine wave for 6ms, Speed variation 3.75m/s 3. Total 18 times (6 directions, 3 repetitions per direction).
Altitude	MIL-STD-883	Standard: 30,000 Ft (Epoxy Sealed Controlled Environment) Optional: Hermetically Sealed (60,000 ft. 1.0 PSI min)
Hermetically Sealed (Optional)		MIL-STD-883 (For Hermetically Sealed Units)




Typical Performance Plots


Insertion Loss @+25°C




Input VSWR @+25°C




Output VSWR @+25°C




Isolation @+25°C



Insertion Loss @-45°C




Input VSWR @-45°C







Output VSWR @-45°C




Isolation @-45°C




Insertion Loss @+85°C




Input VSWR @+85°C



Output VSWR @+85°C




Isolation @+85°C






Switching Speed




Switching Speed



Outline Drawing:

All Dimensions in mm [inches]

[X803]



Truth Table

Control Input TTL								Signal Path State
C8	C7	C6	C5	C4	C3	C2	C1	
1	1	1	1	1	1	1	0	Jo-J1
1	1	1	1	1	1	0	1	Jo-J2
1	1	1	1	1	0	1	1	Jo-J3
1	1	1	1	0	1	1	1	Jo-J4
1	1	1	0	1	1	1	1	Jo-J5
1	1	0	1	1	1	1	1	Jo-J6
1	0	1	1	1	1	1	1	Jo-J7
0	1	1	1	1	1	1	1	Jo-J8

Control Pin Customization available upon request



Important Notice

The information contained herein is believed to be reliable. RF-Lambda makes no warranties regarding the information contained herein. RF-Lambda assumes no responsibility or liability whatsoever for any of the information contained herein. RF-Lambda assumes no responsibility or liability whatsoever for the use of the information contained herein. The information contained herein is provided "AS IS, WHERE IS" and with all faults, and the entire risk associated with such information is entirely with the user. All information contained herein is subject to change without notice. Customers should obtain and verify the latest relevant information before placing orders for RF-Lambda products. The information contained herein or any use of such information does not grant, explicitly or implicitly, to any party any patent rights, licenses, or any other intellectual property rights, whether with regard to such information itself or anything described by such information. RF-Lambda products are not warranted or authorized for use as critical components in medical, life-saving, or life sustaining applications, or other applications where a failure would reasonably be expected to cause severe personal injury or death.