



RF-LAMBDA

LEADER OF RF BROADBAND SOLUTIONS

RFSP2TR0250G

Reflective Coaxial SP2T Switch 2 - 50GHz



Features

- Ultra Wide Band Operation 2-50GHz
- TTL compatible driver included
- Fast Switching Speed
- Low Insertion Loss and High Isolation

Typical Applications

- Wireless Infrastructure
- RF Microwave & VSAT
- Military & Aerospace

Electrical Specifications, TA = +25°C, Vdd = +5V/-12V, TTL = 0 / +5V

Description	PN: RFSP2TR0250G						
	SP2T Reflective Switch						
	Low Power Cold Switching						
Parameters	Min	Typ.	Max	Min	Typ.	Max	Units
Frequency Range	2-26			26-50			GHz
Insertion Loss		2.5	3.2		4.5	5.5	dB
Insertion Loss Temperature Coefficient		0.003			0.003		dB/°C
Isolation	38	45		37	45		dB
Input VSWR		1.8	2.5		2	2.5	:1
Output VSWR		1.8	2.5		2	2.5	:1
RF Input power (CW)			+23			+23	dBm
DC Power Dissipation (CW)		0.5			0.5		W
0.1dB Compression Point (Po.1dB)		23			23		dBm
IIP3		50			45		dBm
Switching Speed			100			100	ns
Weight	0.71						ounces
Impedance	50						Ω
Bias Current (+5V/-12V)	70/80						mA
Input / Output Connectors	2.4mm-Female						
Finish	Gold Plated						
Material	Aluminum						
Seal	Hermetically Sealed (Optional)						

Reflective Coaxial Single Pole Double Throw Switch 2 - 50GHz



RF-LAMBDA

LEADER OF RF BROADBAND SOLUTIONS

RFSP2TR0250G

Absolute Maximum Ratings

Biasing	+5V±10% / -12V±10%
TTL Control Voltage	0~0.8V / 2.8~5V

Note: TTL pins cannot be connected to the negative voltage otherwise the internal driver will be damaged.

Ordering Information

Part No .	ECCN	Description
RFSP2TR0250G	EAR99	SP2T 2-50GHz PIN Diode Switch

Environmental Specifications and Test Standards

Parameter	Standard	Description
Operational Temperature	MIL-STD-39016	-45°C~+85°C (Case Temperature)
Storage Temperature		-50°C~+125°C
Thermal Shock		1 Hour@ -45°C → 1 Hour @ +85°C (5 Cycles)
Random Vibration		Acceleration Spectral Density 6 (m/s) Total 92.6 RMS
Electrical & Temperature Burn In		Temperature +85°C for 72 Hours
Shock		1. Weight >20g, 50g half sine wave for 11ms, Speed variation 3.44m/s 2. Weight <=20g, 100g Half sine wave for 6ms, Speed variation 3.75m/s 3. Total 18 times (6 directions, 3 repetitions per direction).
Altitude	MIL-STD-883	Standard: 30,000 Ft (Epoxy Sealed Controlled Environment) Optional: Hermetically Sealed (60,000 ft. 1.0 PSI min)
Hermetically Sealed (Optional)		MIL-STD-883 (For Hermetically Sealed Units)

Reflective Coaxial Single Pole Double Throw Switch 2 - 50GHz




RF-LAMBDA

LEADER OF RF BROADBAND SOLUTIONS


RFSP2TR0250G

Typical Performance Plots


Insertion Loss @+25°C




Input VSWR @+25°C




Output VSWR @+25°C




Isolation @+25°C




Insertion Loss @-45°C




Input VSWR @-45°C



Output VSWR @-45°C



Isolation @-45°C



Reflective Coaxial Single Pole Double Throw Switch 2 - 50GHz




RF-LAMBDA


LEADER OF RF BROADBAND SOLUTIONS

RFSP2TR0250G


Insertion Loss @+85°C




Input VSWR @+85°C




Output VSWR @+85°C




Isolation @+85°C



Switching Speed



Switching Speed




Reflective Coaxial Single Pole Double Throw Switch 2 - 50GHz



Outline Drawing:

All Dimensions in mm [inches]



Truth Table

Control Input TTL		Signal Path State
C2	C1	
1	0	J0-J1
0	1	J0-J2

Control Pin Customization
available upon request



Important Notice

The information contained herein is believed to be reliable. RF-Lambda makes no warranties regarding the information contained herein. RF-Lambda assumes no responsibility or liability whatsoever for any of the information contained herein. RF-Lambda assumes no responsibility or liability whatsoever for the use of the information contained herein. The information contained herein is provided "AS IS, WHERE IS" and with all faults, and the entire risk associated with such information is entirely with the user. All information contained herein is subject to change without notice. Customers should obtain and verify the latest relevant information before placing orders for RF-Lambda products. The information contained herein or any use of such information does not grant, explicitly or implicitly, to any party any patent rights, licenses, or any other intellectual property rights, whether with regard to such information itself or anything described by such information. RF-Lambda products are not warranted or authorized for use as critical components in medical, life-saving, or life sustaining applications, or other applications where a failure would reasonably be expected to cause severe personal injury or death.