



USB Absorptive Coaxial SP2T Switch 0.02 - 18GHz



Features

- Wide Band Operation 0.02-18GHz
- USB Controlled and Powered.
- Low Insertion Loss and High Isolation
- Customization available upon request
- Control SW included.

Typical Applications

- Automated Test
- Aerospace and military applications

Electrical Specifications, TA = +25 °C, USB Powered

Description	PN: RFSP2TA0018GUSB										
	SP2T Absorptive Switch										
	Low Power Cold Switching										
Parameters	Min	Typ.	Max	Min	Typ.	Max	Min	Typ.	Max	Units	
Frequency Range	0.02-8			8-12			12-18			GHz	
Insertion Loss			3.2			4			4.5	dB	
Insertion Loss Temperature Coefficient		0.003			0.003			0.003		dB/°C	
Isolation	65			60			60			dB	
Input VSWR			2			2			2	:1	
Output VSWR			2			2			2	:1	
RF Input power (CW)			1			1			1	W	
DC Power Dissipation		0.55			0.55			0.55		W	
0.1dB Compression Point (P 0.1dB)		30			30			30		dBm	
IIP3		55			55			55		dBm	
Weight	1.5									ounces	
Impedance	50									Ω	
Bias Current	110									mA	
Control Interface	USB 2.0 (Control Cable Included)										
Switching Speed	200~300 ms										
Input / Output Connectors	SMA-Female										
Finishing	Nickel Plated										
Material	Aluminum										

USB Absorptive Coaxial Single Pole Double Throw Switch 0.02 - 18GHz



Absolute Maximum Ratings

RF Input Power	+30dBm
----------------	--------

Ordering Information

Part No.	ECCN	Description
RFSP2TA0018GUSB	EAR99	SP2T 0.02-18GHz PIN Diode Switch

Environmental Specifications

Operational Temperature (°C)	-45 ~ +85
Storage Temperature (°C)	-50 ~ +125
Vibration	25g RMS (15 degrees 2KHz) endurance, 1 hour per axis
Shock	20G for 11msec half sine wave, 3 axis both directions

USB Absorptive Coaxial Single Pole Double Throw Switch 0.02 - 18GHz




RF-LAMBDA

LEADER OF RF BROADBAND SOLUTIONS

RFSP2TA0018GUSB

Outline Drawing:


All Dimensions in mm [inches]



USB Absorptive Coaxial Single Pole Double Throw Switch 0.02 - 18GHz



Figure 1 (USB Control Panel)







RF-LAMBDA

LEADER OF RF BROADBAND SOLUTIONS

RFSP2TA0018GUSB



USB Absorptive Coaxial Single Pole Double Throw Switch 0.02 - 18GHz

Important Notice

The information contained herein is believed to be reliable. RF-Lambda makes no warranties regarding the information contained herein. RF-Lambda assumes no responsibility or liability whatsoever for any of the information contained herein. RF-Lambda assumes no responsibility or liability whatsoever for the use of the information contained herein. The information contained herein is provided "AS IS, WHERE IS" and with all faults, and the entire risk associated with such information is entirely with the user. All information contained herein is subject to change without notice. Customers should obtain and verify the latest relevant information before placing orders for RF-Lambda products. The information contained herein or any use of such information does not grant, explicitly or implicitly, to any party any patent rights, licenses, or any other intellectual property rights, whether with regard to such information itself or anything described by such information. RF-Lambda products are not warranted or authorized for use as critical components in medical, life-saving, or life sustaining applications, or other applications where a failure would reasonably be expected to cause severe personal injury or death.