



Electrical:

Frequency Range:

Coupling:

Insertion Loss:

Coupling Flatness

Directivity:

VSWR:

Power Forward

Power Reflected:

Power Peak:

Weight:

Operating Temperature:

Input power is rated for load VSWR better than 1.20:1.

Insertion loss does not include coupling loss.

Coupling loss for 20 dB is 0.044 dB.

Coupling is with respect to output.

Specifications:

6.0 – 40.0

20.0 ± 1.00

1.20

± 1.00

12

9

1.70:1

20

20

3

0.8 / 22.7

-40°C to +85°C

Ghz

dB

dB Max

dB Max

dB Typ

dB Min

Max

Watts

Watts

KW

Ounces / grams

SigaTek

SC2019118

Dimensions are in inches and (mm)

Decimal Tolerance:

2 place +- 0.020

3 place +- 0.010

423 Black Oak Ridge Rd.

Wayne, NJ 07470

Ph: 973-706-8475, Fax: 973-832-4435

www.sigatek.com

Directional Coupler 20 dB
2.92mm Connectors

CAGE CODE : 69UC1

Notes: All dimensions are typical unless they are specified.

Specifications are subject to change at any time without any notice.

Copy or distribution of this drawing is not allowed without Sigatek's approval.