

SPECIFICATION SHEET**JFW MODEL 50S-1638+XX****1P6T NORMALLY OPENED SELF TERMINATING
ELECTROMECHANICAL RF SWITCH**

JFW Industries, Inc.
Phone: 317-887-1340
sales@jfwindustries.com
www.jfwindustries.com

Frequency Range DC-18 GHz

Configuration 1P6T Normally Open Self Terminating

Impedance 50 Ohms nominal

VSWR 1.2:1 maximum DC-4 GHz
1.3:1 maximum 4-8 GHz
1.4:1 maximum 8-12 GHz
1.5:1 maximum 12-18 GHz

Insertion Loss 0.20 dB maximum DC-4 GHz
0.30 dB maximum 4-8 GHz
0.40 dB maximum 8-12 GHz
0.50 dB maximum 12-18 GHz

Isolation 80 dB minimum DC-4 GHz
70 dB minimum 4-8 GHz
65 dB minimum 8-12 GHz
60 dB minimum 12-18 GHz

Switching Speed 15 milliseconds

RF Input Power* 500 Watts average DC-100 MHz
400 Watts average 100-200MHz
300 Watts average 200-500MHz
200 Watts average 500-1000MHz
100 Watts average 1-4 GHz
90 Watts average 4-8 GHz
70 Watts average 8-12 GHz
60 Watts average 12-18 GHz
*2 Watts average for self terminations

Control (6 lines)
(Only one active at a time) +XX is either +12,+15 or +28:

+12 Vdc @ 400 mA nominal (11-14Vdc)
+15 Vdc @ 375 mA nominal (13-17Vdc)
+28 Vdc @ 160 mA nominal (24-32Vdc)

DC Connector Solder Terminals

RF Connector SMA female

Operating Temperature Range -25°C to +65°C

Lifetime 1 million cycles minimum

Physical Size See outline drawing 092-5913

Add (-NR) for NON-RoHS version. (I.e. 50S-1638+12-NR SMA)

ECR/ECN #	DATE	REV	APPR / DATE	ECR/ECN #	DATE	REV	APPR / DATE
	09/25/2008		BAC 09/25/2008				
24842	01/07/2015	A	BAC 01/07/2015				
28937	08/08/2018	B	TRS 08/08/2018				