


## WR-34 Waveguide Spacer, 208 Mils, 3/8 $\lambda$ g

### Description:

**SWI-34208-SB** is a 0.208" thick, 3/8 wavelength, instrumentation grade WR-34 Band waveguide spacer (shim) with WR-34 window and UG-1530/U square flange. The spacer is manufactured with a precision machining process to ensure high quality and ruggedness. The spacer is offered to cover the frequency range of 22 to 33 GHz.



### Features:

- Frequency Range: 22 to 33 GHz
- 3/8 Wavelength
- Low Insertion Loss
- Instrumentation Grade

### Applications:

- Module Tuning
- Sub-assemblies
- Mechanical Fitting
- VNA Calibration

### Mechanical Specifications:

Item	Specification
Waveguide Size	WR-34 Waveguide with UG-1530/U Flange
Material	Brass
Finish	Gold Plated
Weight	0.7 Oz
Insertion Length	0.208" (L)
Outline	WI-3L

**Mechanical Outline:** (Unless otherwise specified, all dimensions are in inches [millimeters])



### Note:

- Length "L" is customizable.
- SAGE Millimeter, Inc. reserves the right to change the information presented without notice.



www.sagemillimeter.com | 3043 Kashiwa Street, Torrance, CA 90505  
Phone: 424-757-0168 | Fax: 424-757-0188 | Email: sales@sagemillimeter.com