#### **DESCRIPTION**

PMI MODEL: CL7G-2G-CD-SFF IS A BANDPASS FILTER CENTERED AT 7.0 GHz WITH A NOMINAL BANDWIDTH OF 2.0 GHz. THE FILTER IS MACHINED, SILVER PLATED, AND OUTFITTED WITH SMA FEMALE CONNECTORS TO PROVIDE THE HIGHEST POSSIBLE Q.

REVISIONS				
ZONE	REV.	DESCRIPTION	DATE	APPROVED
	-	PRELIMINARY	02/14/17	<b>SP</b>

## MECHANICAL OUTLINE


#### **SPECIFICATIONS**

----- 7.0 GHz • CENTER FREQUENCY: -----

• -3 dB BANDWIDTH: ----- 2.0 GHz

------ -35 dBc min. @ 167% BW • REJECTION: -----

CONNECTORS: ------ SMA FEMALE



### **ENVIRONMENTAL RATINGS**

• TEMPERATURE: ----- -55 °C TO +85 °C (OPERATING) -65 °C TO +125 °C (STORAGE) • HUMIDITY: ----- MIL-STD-202, METHOD 103B COND. B SHOCK: ----- MIL-STD-202, METHOD 213B COND. B

VIBRATION: ----- MIL-STD-202, METHOD 204D COND. B

• ALTITUDE: ----- MIL-STD-202, METHOD 105C COND. B TEMPERATURE CYCLE: ------ MIL-STD-202. METHOD 107D COND. A

ALL DIMENSIONS ARE IN INCHES (mm) TOLERANCES:

X.XXX

# PLANAR MONOLITHICS INDUSTRIES, INC.

7311-F GROVE ROAD FREDERICK, MARYLAND 21704 USA TEL: (301)-662-5019, FAX: (301)-662-1731 WEB: www.pmi-rf.com, EMAIL: sales@pmi-rf.com

ISO 9001 CERTIFIED



TITLE PRODUCT FEATURE APPROVALS DATE CL-3D1G-400-CD-SFF EMF. 02/14/17 CHECKED SIZE FSCM NO. Α 05XQ0 **PRELIMINARY** ISSUED SCALE N:S SHEET 1 OF 1

NOTE: SPECIFICATIONS WILL VARY OVER OPERATING TEMPERATURE NOTE: THE ABOVE SPECIFICATIONS ARE SUBJECT TO CHANGE OR REVISION

PMI CONFIDENTIAL AND PROPRIETARY