


DESCRIPTION:

PMI model number 7BP960-53D4-CD-SFF is a Narrow Bandpass filter with SMA Connectors.
connectors in and out.

SPECIFICATIONS:

- CENTER FREQUENCY 960 MHz (NOM)
 - BANDWIDTH 53.4 MHz (NOM)
 - INSERTION LOSS (PASSBAND) 6 dB (MAX)
 - STOPBAND ATTENUATION @ DC - 840 MHz 70 dB (MIN)
 - STOPBAND ATTENUATION @ 1080 - 2400 MHz 70 dB (MIN)
 - VSWR IN THE BANDWIDTH 1.5:1 (MAX)
 - INPUT POWER +30 dB (MAX)
 - IMPEDANCE (SOURCE LOAD) 50 ohms (NOM)
-
- CONNECTORS: SMA FEMALE CONNECTORS
 - SIZE 2.00" (L) x 0.50" (W) x 0.50" (H)
 - WEIGHT 1 OZ. TYP.



ENVIRONMENTAL RATINGS:

- TEMPERATURE: -55°C TO +85°C (OPERATING)
-65°C TO +125°C (STORAGE)
- HUMIDITY: MIL-STD-202F, METHOD 103B COND. B
- SHOCK: MIL-STD-202F, METHOD 213B COND. B
- VIBRATION: MIL-STD-202F, METHOD 204D COND. B
- ALTITUDE: MIL-STD-202F, METHOD 105C COND. B
- SALT FOG: MIL-STD-202F, METHOD 107D COND. A
- FUNGUS: MIL-STD-810C, METHOD 508.2
- TEMPERATURE CYCLE: MIL-STD-202F, METHOD 107

NOTE: THE ABOVE SPECIFICATIONS ARE SUBJECT TO CHANGE OR REVISION

REVISIONS				
ZONE	REV.	DESCRIPTION	DATE	APPROVED
	—	PRELIMINARY	08/15/14	

PMI CONFIDENTIAL AND PROPRIETARY

PLANAR MONOLITHICS INDUSTRIES, INC.

7311-F GROVE ROAD
FREDERICK, MARYLAND 21704 USA
TEL: 301-662-5019 FAX: 301-662-1731
WEBSITE: www.pmi-rf.com
E-MAIL: sales@pmi-rf.com
ISO 9001 CERTIFIED



APPROVALS		DATE		TITLE	
DRAWN <i>JRP</i>		08/15/14		OUTLINE DRAWING	
CHECKED				7BP960-53D4-CD-SFF	
ISSUED				PRELIMINARY	
SIZE A		FSCM NO. 05XQ0		DWG NO.	
SCALE N:S				SHEET 1 OF 1	