

DESCRIPTION:

PMI MODEL NUMBER PDVAN-8018-60-8 IS AN 8 BIT PROGRAMMABLE 60 DB PIN DIODE ATTENUATOR WITH STEP RESOLUTION AS LOW AS 0.25 DB OVER THE FREQUENCY RANGE OF 8.0 GHz TO 18.0 GHz.

SPECIFICATIONS:

- FREQUENCY: 8.0 GHz TO 18.0 GHz
- MEAN ATTENUATION RANGE: 60dB
- LSB: 0.25dB
- INSERTION LOSS: 3.7dB MAX
- VSWR: 2.0:1 MAX
- POWER RATING: +20dBm CW MIN (Operating)
+30dBm CW MAX (Survival)
- ATTENUATION FLATNESS:
 - @ 10 dB ±0.8 dB
 - @ 20dB ±1.1 dB
 - @ 40dB ±1.5 dB
 - @ 60dB ±1.6 dB
- SWITCHING TIME 500 nsec MAX
- DIGITAL CONTROL 8 BIT Binary TTL
- INPUT TRACKING: MONOTONIC
- POWER SUPPLY +12V to +15V @ 150mA MAX
-12V to -15V @ 75mA MAX
- PWR/CTL CONNECTORS 15 PIN Micro-D-Female (MATING CONNECTOR SUPPLIED)
- RF CONNECTORS SMA - Female
- FINISH PAINTED BLUE
- SIZE (L) 2.00" X (W) 1.80" X(H) 0.50"



ENVIRONMENTAL RATINGS:

- TEMPERATURE: -55°C TO +85°C (OPERATING)
-65°C TO +125°C (STORAGE)
- HUMIDITY: MIL-STD-202F, METHOD 103B COND. B
- SHOCK: MIL-STD-202F, METHOD 213B COND. B
- VIBRATION: MIL-STD-202F, METHOD 204D COND. B
- ALTITUDE: MIL-STD-202F, METHOD 105C COND. B
- TEMPERATURE CYCLE: MIL-STD-202F, METHOD 107

NOTE: THE ABOVE SPECIFICATIONS ARE SUBJECT TO CHANGE OR REVISION

PIN NO:	J3 PIN FUNCTIONS
1	N/C
2	N/C or Latching Strobe Input *
3	N/C
4	GND
5	0.25dB (LSB)
6	0.5dB
7	1.0dB
8	2.0dB
9	4.0dB
10	8.0dB
11	16.0dB
12	32dB (MSB)
13	+VDC
14	-VDC
15	N/C

* OPTIONAL



PMI CONFIDENTIAL AND PROPRIETARY

- LOGIC INPUT
LOGIC "0" (BIT OFF) -0.3 to +0.8V
LOGIC "1" (BIT ON) +2.0 to +5.0V

ALL DIMENSIONS ARE IN INCHES
TOLERANCES:
X.XX ±0.020
X.XXX ±0.010

APPROVALS

DATE

DRAWN

6/24/14

CHECKED

ISSUED

TITLE

PRODUCT FEATURE

PDVAN-8018-60-8

SIZE

FSCM NO.

DWG NO.

REV.

A

05XQ0

PRELIMINARY

-

SCALE

N:S

SHEET

1 OF 1

7311-F GROVE ROAD

FREDERICK, MARYLAND 21704 USA

TEL: 301-662-5019 FAX: 301-662-1731

WEBSITE: www.pmi-rf.com

E-MAIL: sales@pmi-rf.com

ISO 9001:2008 CERTIFIED

